



# FINISHING

## FINISHING TABLES WITHOUT BOILER MRP - A/AS/VAS

### CHARACTERISTICS

- 3 variants
  - A: vacuum
  - S: blowing
  - V: up steaming
- Vacuum ironing table + iron, with electrically heated board and suction.
- Adjustable temperature of the board by means of a thermostat.
- Built-in single phase suction unit.
- Working table dimensions (1.200 x 400 x 250 mm).
- Works by means of a pedal.
- Electrical heating.

### OPTIONS

- Sleeve arm.
- Steam gun.
- Sliding trolley with light.



MRP - AS

## TECHNICAL DATA

### FINISHING TABLES WITHOUT BOILER | MRP-A/AS/VAS

	UNIT.	MRP-A	MRP-AS	MRP-VAS
<b>CAPACITY</b>				
Boiler	-	No	No	No
Boiler capacity	l	-	-	-
Board dimensions	mm	1.200 x 400 x 250	1.200 x 400 x 270	1.200 x 400 x 250
<b>OPTIONS</b>				
Swinging arm with suction and heated sleeve shape	-	Opt	Opt	Opt
Steam gun	-	Opt	Opt	Opt
Sliding trolley with balancer and lighting	-	Opt	Opt	Opt
Second steam iron assembly	-	Opt	Opt	Opt
<b>POWER</b>				
Vacuum Motor	kW	0,45	0,45	0,45
Pump Motor	kW	-	-	-
Iron Heater	kW	0,83	0,83	0,83
Board heater	kW	1	1	-
Sleeve-arm heater (option)	kW	0,09	0,09	0,09
<b>CONNECTIONS</b>				
Ø Water inlet	BSP	-	-	-
Ø Steam inlet	BSP	1/4"	1/4"	3/8"
Steam pressure	BAR	-	-	-
Steam Consumption	Kg/h	5	5	10-15
Ø Air inlet	BSP	-	-	-
Air pressure	BAR	-	-	-
Air Consumption	NI/m	-	-	5
<b>DIMENSIONES / DIMENSIONES CON EMBALAJE</b>				
Width / Width	mm	1.480/1.520	1.500/1.520	1.680/1.880
Depth / Depth	mm	480/580	600/580	580/680
Height / Height	mm	930/1.120	1.800/1.120	920/1.270
Net weight / Gross weight	kg	66/82	78/94	110/134
Volume	m <sup>3</sup>	3,20/5,19	3,88/6,23	4,68/7,43
<b>OTHERS</b>				
Voltage	Hz	230V   50	230V   50	230V   50
Sound level	dB	68	70	75



# FINISHING

## FINISHING TABLES WITH BOILER MRP - AD / MRP-A/AS/VAS - C

### CHARACTERISTICS

#### 3 VARIANTS:

- A: vacuum
- S: blowing
- V: up steaming

#### MRP-AD

- Utility ironing table with electrically heated board and suction unit.
- Version with built-in electric steam boiler, water pump, water feeding tank and electric steam iron.
- Built-in suction unit controlled by foot pedal.
- Adjustable board temperature by thermostat.
- Pedals on both sides of the table.
- Electric boiler with water feeding and automatic steam production. Working pressure: 2,6 bar.
- Manual feeding of water tank.
- Voltage: 230V | 50Hz

#### MRP-A/AS/VAS - C

- Utility ironing table with suction and electrically heated board, controlled by a thermostat.
- Built-in electric steam boiler.
- With standard board (1200x400x250).
- Automatic water feeding.

### OPTIONS

- Sleeve arm.
- Steam gun.
- Sliding trolley with light.
- Second iron.



## TECHNICAL DATA

### FINISHING TABLES WITH BOILER | MRP - AD / MRP-A/AS/VAS - C

	UNIT.	MRP-AD	MRP-A-C	MRP-AS-C	MRP-VAS-C
<b>CAPACITY</b>					
Boiler	-	Yes	Yes	Yes	Yes
Boiler capacity	l	4	5	5	7
Board dimensions	mm	1.100 x 380 x 270	1.200 x 400 x 250	1.200 x 400 x 270	1.200 x 400 x 250
<b>OPTIONS</b>					
Swinging arm with suction and heated sleeve shape	-	Opt	Opt	Opt	Opt
Steam gun	-	-	Opt	Opt	Opt
Sliding trolley with balancer and lighting	-	-	Opt	Opt	Opt
Second steam iron assembly	-	-	Opt	Opt	Opt
<b>POWER</b>					
Vacuum Motor	kW	0,13	0,45	0,45	0,45
Pump Motor	kW	-	-	-	0,75
Iron Heater	kW	0,8	0,83	0,83	0,83
Board heater	kW	0,7	1	1	-
Boiler Heater	kW	1,45	3,9	3,9	6-7,5
Sleeve-arm heater (option)	kW	0,09	0,09	0,09	0,09
<b>CONNECTIONS</b>					
Ø Water inlet	BSP	-	3/8"	3/8"	3/8"
Ø Boiler exhaust (with boiler)	BSP	-	3/8"	3/8"	3/8"
Ø Steam inlet	BSP	-	-	-	-
Steam pressure	BAR	2,8	2,8	2,6	4,5
Steam Consumption	Kg/h	-	-	-	-
Ø Air inlet	BSP	-	-	-	1,4"
Air pressure	BAR	-	-	-	4-8
Air Consumption	NI/m	-	-	-	5
<b>DIMENSIONES / DIMENSIONES CON EMBALAJE</b>					
Width / Width	mm	1.380/1.300	1.550/1.520	1.500/1.520	1.680/1.880
Depth / Depth	mm	380/540	580/580	600/580	580/680
Height / Height	mm	930/1.160	950/1.140	1.800/1.120	920/1.270
Net weight / Gross weight	kg	43/57	87/103	100/116	141/165
Volume	m <sup>3</sup>	0,49/0,81	0,85/1,01	1,62/0,99	0,90/1,62
<b>OTHERS</b>					
Voltage	Hz	230V I 50	230/400V III 50	230V I 230/400V III 50	230/400V III 50
Sound level	dB	70	68	70	75